



ASCOLITE[®]
HEAT SEALED BUTTON SECURITY

Button Shank Regulator Clamp

New
version



Attaching any type of sewn button requires the correct minimum gap between the button and the fabric to enable a clean and tightly wrapped button shank.

Guidance for minimum shank gap

(Space between button and fabric)

Garment types	Shank gap (before wrapping)	Recommended Nr of wraps
Jackets	4 mm	25–30
Trousers	3–3,5 mm	20
Shirts	2,5–3 mm	10–12
Outerwear	3–3,5 mm	25–40
Leather	3–3,5 mm	30–40



The **Ascolite “Button Shank Regulator”** makes it very easy to adjust the required shank gap between attached button and fabric.

Advantages of using **Ascolite “Button Shank Regulator”**

- Enough & consistent space for button shank wrapping with **Ascolite® TF-Yarn**
- Results in a slim, clean and secure wrap on button shank
- Allows buttons hole to close well under button without bulges
- Makes buttoning up and unbuttoning easier

ASCOLITE OFFICES AND SERVICE CENTERS

HEAD OFFICE ASCOLITE AG SWITZERLAND, TEL. +41 44 912 00 00

HONG KONG OFFICE TEL. +852 2343 3262 **GERMANY OFFICE** TEL. +49 811 555444 90

UK OFFICE TEL. +44 191 680 8628 **CHINA OFFICE** TEL. +86 755 2594 4969 **VIETNAM OFFICE** TEL: +84 2 8629 55052

INDONESIA OFFICE TEL. +62 812 9155368 **BANGLADESH OFFICE** TEL. +8802 4895 5397 **KOREA OFFICE** TEL. +82 31 926 3031

INFO@ASCOLITE.COM WWW.ASCOLITE.COM