



ASCOLITE[®]
HEAT SEALED BUTTON SECURITY

Button Shank Regulator Clamp

New
version



Attaching any type of sewn button requires the correct minimum gap between the button and the fabric to enable a clean and tight button shank wrapping.

Instruction how to maintain the minimal distance from button to fabric:

Garment types:	Shank length (before wrapping)	Number of wraps
Jackets	3 mm	25–30
Trousers	2,5–3 mm	20
Shirts	2–2,5 mm	10–12
Outerwear	3 mm	25–40
Leather	3–3,5 mm	30–40



The **Ascolite Button Shank Regulator** makes it very easy to adjust the required gap between the button attached and the fabric. The Ascolite Button Shank Regulator:

- makes buttoning up and unbuttoning easier
- allows the button hole to close well under the button
- to let enough space for button shank wrapping with Ascolite® TF yarn
- to get a slim, safe and clean Ascolite® button shank

ASCOLITE OFFICES AND SERVICE CENTERS

HEAD OFFICE ASCOLITE AG SWITZERLAND, TEL. +41 44 912 00 00

HONG KONG OFFICE TEL. +852 2343 3262 **GERMANY OFFICE** TEL. +49 811 555444 90

UK OFFICE TEL. +44 191 680 8628 **SHANGHAI OFFICE** TEL. +86 21 5416 0961 **CHINA OFFICE** TEL. +86 755 2594 4969

VIETNAM OFFICE TEL: +84 2 8629 55052 **INDONESIA OFFICE** TEL. +62 812 9155268 **USA OFFICE** TEL +1 914 522 9896

BANGLADESH OFFICE TEL. +8802 4895 5397 **INDIA OFFICE** TEL: +91 7982664099 **KOREA OFFICE** TEL. +82 31 926 3031

INFO@ASCOLITE.COM WWW.ASCOLITE.COM